


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	17-0028	UPDATED TO NEW DRAFTING STANDARD. -1, -3, -5, -11 ADDED FINISH SPEC. QMSI-6.2.2, B.O. REV D. -1 CH'D DIM'S WAS (Ø1.375) IS Ø1.38, WAS 5/16-24 UNF THRU ALL IS 5/16-24 UNF -2B THRU ALL CH'D MATERIAL WAS 1018 IS 1018/1020 CR. -3, -11 CH'D MATERIAL WAS 4140 Q&T IS 4140/4142, ADDED HEAT TREAT RC 25-32. -3 CH'D DIM WAS (Ø1.38) IS Ø1.38. -5 CH'D DIM WAS (Ø1.375) IS Ø1.38. -7, -9 CH'D MATERIAL WAS BRONZE IS BRONZE 660. -11 CH'D DIM'S WAS 5/16-24 IS 5/16-24 UNF -2A, WAS 1/4-20 IS 1/4-20 UNC -2A. -25 CH'D B/O P/N WAS APPLIED SMALLEY RING CO. #CS112-H2).	2/28/2017	RJC	JAG
3	17-0087	-1 CH'D DIM'S WAS .400 IS .40, WAS .535 IS .54, WAS .850 IS .85. -3 DELETED ENGRAVE P/N NOTE.	4/17/2017	RJC	JAG



BEARING #  
NHBY6V204  
109-0133-11-101





ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.				
			-1	1	SPRING TENSIONER	1018/1020 CR		2	<b>PORTABLE BEARING CUTTERS</b>			
			-3	1	SEAT	4140/4142		3				
			-5	1	CUTTER	0-1 DRILL ROD		4	<b>RBW1006-P</b>			
			-7	1	GUIDE	BRONZE 660		5				
			-9	1	BUSHING	BRONZE 660		6	<b>REV 3</b>			
			-11	1	STUD	4140/4142		7				
		B/O	-15	1	SPRIAL RETAINING RING	STEEL	Ø7/16 SHAFT (MCMMASTER-CARR #91665A350)	1	<b>SPEC</b>			
		B/O	-17	1	THRUST BEARING		Ø5/8 ID X 1-1/8 OD X 5/64 (APPLIED #NTA-1018)	1				
		B/O	-19	2	THRUST WASHER		Ø5/8 ID X 1-1/8 OD X 1/16 (APPLIED #TRB-1018)	1	<b>DRAWN BY: GILBERT</b>			
		B/O	-27	1	SWIVEL HEX FLANGE NUT	STEEL	1/4-20 UNC (MCMMASTER-CARR #90477A029)	1				
		B/O	-25	1	WAVE SPRING	STEEL	(APPLIED SMALLEY RING CO # CS112-H2)	1	<b>CHECKED: DUERFELDT</b>			
		B/O	-29	1	TOOTH GUARD (FOR SHIPPING ONLY)	VINYL	Ø15/16 ID X 5/8 LONG	1				
		B/O	-23	1	SPANNER WRENCH		Ø1-1/2 (MCMMASTER-CARR #5475A13)	N/S	<b>OPPS APPR: ANDERSON</b>			
									<b>QA APPR: LINDSAY</b>			
									<b>APPROVED: GILBERT</b>			
									<b>SCALE 1:1.5</b>			
									<b>DATE 9/26/2013</b>			
									<b>SHEET 1 OF 7</b>			

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES  
.XXX ± .005 FRACTIONS ± 1/8  
.XX ± .01 ANGLES ± 5°  
.X ± .1 SURFACES = 125°  
1. BREAK ALL SHARP EDGES  
.015 x 45° OR .015R  
2. DIMENSIONAL LIMITS APPLY  
AFTER PLATING  
3. INTERPRET DIM AND TOL PER  
ASME Y14.5M-2009

USED ON MODEL

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	17-0028	-1 CH'D DIM'S WAS (Ø1.375) IS Ø1.38, WAS 5/16-24 UNF THRU ALL IS 5/16-24 UNF -2B THRU ALL. CH'D MATERIAL WAS 1018 IS 1018/1020 CR, ADDED FINISH SPEC. QMSI-6.2.2, B.O. REV D.	2/28/2017	RJC	JAG
3	17-0087	-1 CH'D DIM'S WAS .400 IS .40, WAS .535 IS .54, WAS .850 IS .85.	4/17/2017	RJC	JAG






SECTION A-A

-1  
SPRING TENSIONER

<b>DART AEROSPACE</b>	
TITLE <b>PORTABLE BEARING CUTTER</b>	
DWG NO. <b>RBW1006-P-1</b>	REV <b>3</b>
MAT'L 1018/1020 CR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX ± .005 FRACTIONS ± 1/8
FINISH BLACK OXIDE	.XX ± .01 ANGLES ± 5°
SPEC QMSI-6.2.2, B.O. REV D	.X ± .1 SURFACES = 125° ✓
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	
SCALE 1:1	DATE 9/26/2013 SHEET 2 OF 7

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	17-0028	-3 CH'D DIM WAS (Ø1.38) IS Ø1.38. CH'D MATERIAL WAS 4140 Q&T IS 4140/4142. ADDED HEAT TREAT RC 25-32. ADDED FINISH SPEC. QMSI-6.2.2, B.O. REV D.	2/28/2017	RJC	JAG
3	17-0087	-3 DELETED ENGRAVE P/N NOTE.	4/17/2017	RJC	JAG



SECTION B-B




(-3)

SEAT


<b>DART AEROSPACE</b>	
TITLE <b>PORTABLE BEARING CUTTER</b>	
DWG NO. <b>RBW1006-P-3</b>	REV <b>3</b>
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 25-32	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2, B.O. REV D	.XX ± .01 ANGLES ± .5°
DRAWN BY: GILBERT	.X ± .1 SURFACES = 125°
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 1:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 9/26/2013	USED ON MODEL
SHEET 3 OF 7	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.


REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
2	17-0028	-5 CH'D DIM WAS (Ø1.375) IS Ø1.38. ADDED FINISH SPEC. QMSI-6.2.2, B.O. REV D.	2/28/2017	RJC
				JAG




DETAIL VIEW  
SCALE 2 : 1  
TYP TO 6 TEETH



(5)  
CUTTER






SECTION D-D



<b>DART AEROSPACE</b>	
TITLE <b>PORTABLE BEARING CUTTER</b>	
DWG NO. <b>RBW1006-P-5</b>	REV <b>3</b>
MAT'L 0-1 DRILL ROD HEAT TREAT 55-60 HRC FINISH BLACK OXIDE SPEC QMSI-6.2.2, B.O. REV D	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125 ✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: GILBERT CHECKED: DUERFELDT OPPTS APPR: ANDERSON QA APPR: LINDSAY APPROVED: GILBERT	
USED ON MODEL	
SCALE 1:1	DATE 9/26/2013
SHEET 4 OF 7	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	17-0028	-7 CH'D MATERIAL WAS BRONZE IS BRONZE 660.	2/28/2017	RJC	JAG






(-7)  
GUIDE

<b>DART</b> AEROSPACE	
TITLE <b>PORTABLE BEARING CUTTER</b>	
DWG NO. <b>RBW1006-P-7</b>	REV <b>3</b>
MAT'L <b>BRONZE 660</b>	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TREAT <b></b>	.XXX ± .005 FRACTIONS ± 1/8
FINISH <b></b>	.XX ± .01 ANGLES ± .5°
SPEC <b></b>	.X ± .1 SURFACES = 125° ✓
DRAWN BY: <b>GILBERT</b>	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: <b>DUERFELDT</b>	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: <b>ANDERSON</b>	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: <b>LINDSAY</b>	USED ON MODEL
APPROVED: <b>GILBERT</b>	
SCALE <b>2:1</b>	DATE <b>9/26/2013</b>
SHEET 5 OF 7	



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	17-0028	-9 CH'D MATERIAL WAS BRONZE IS BRONZE 660.	2/28/2017	RJC	JAG





(-9)

BUSHING

<b>DART</b> AEROSPACE	
TITLE <b>PORTABLE BEARING CUTTER</b>	
DWG NO. <b>RBW1006-P-9</b>	REV <b>3</b>
MAT'L <b>BRONZE 660</b>	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TREAT <b></b>	.XXX ± .005 FRACTIONS ± 1/8
FINISH <b></b>	.XX ± .01 ANGLES ± .5°
SPEC <b></b>	.X ± .1 SURFACES = 125° ✓
DRAWN BY: <b>GILBERT</b>	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: <b>DUERFELDT</b>	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: <b>ANDERSON</b>	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: <b>LINDSAY</b>	USED ON MODEL
APPROVED: <b>GILBERT</b>	
SCALE <b>2:1</b>	DATE <b>9/26/2013</b>
SHEET 6 OF 7	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	17-0028	-11 CH'D DIM'S WAS 5/16-24 IS 5/16-24 UNF -2A, WAS 1/4-20 IS 1/4-20 UNC -2A, CH'D MATERIAL WAS 4140 Q&T IS 4140/4142, ADDED HEAT TREAT RC 25-32, ADDED FINISH SPEC. QMSI-6.2.2, B.O. REV D.	2/28/2017	RJC	JAG



(-11)

STUD

<b>DART</b> AEROSPACE	
TITLE <b>PORTABLE BEARING CUTTER</b>	
DWG NO. <b>RBW1006-P-11</b>	REV <b>3</b>
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 25-32	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2, B.O. REV D	.XX ± .01 ANGLES ± 5°
DRAWN BY: GILBERT	.X ± .1 SURFACES = 125
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 1:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 9/26/2013	USED ON MODEL
SHEET 7 OF 7	